

**Ø 4****0.8 mm (0.03")**

●/-	●/-	-
NPN	PNP	AC
KIB-D04NS/ 0.8-KLSM8	KIB-D04PS/ 0.8-KLSM8	-
650.2399.015	650.2999.017	
263/4	263/1	

-/●	●/-	-
-	-	-

Ø 6.5**1.5 mm (0.06")**

●/-	●/-	-
NPN	PNP	AC
KIB-D06NS/ 1.5-KL2	KIB-D06PS/ 1.5-KL2	-
650.2399.009	650.2999.010	
263/4	263/1	

-/●	●/-	-
-	-	-

-	KIB-D06PÖ/ 1.5-KL2	-
-	650.2799.011	
-	263/2	
-	-/●	-

Ø 6.5**1.5 mm (0.06")**

-	●/-	-
NPN	PNP	AC
-	KIB-D06PS/ 1.5-K2VPU	-
-	650.2999.034	
-	263/1	

-	●/-	-
-	-	-

10-30 V	10-30 V	-
-/200 mA	-/200 mA	-
3000 Hz	3000 Hz	-
●	●	-
●/-	●/-	-
-	-	-

10-36 V	10-36 V	-
-/200 mA	-/200 mA	-
1000 Hz	1000 Hz	-
●	●	-
●/-	●/-	-
-	-	-

-	10-36 V	-
-	-/200 mA	-
-	1000 Hz	-
-	●	-
-	-	-
-	-	-

-25 °C/+70 °C	-25 °C/+70 °C	-
-13 °F/+158 °F	-13 °F/+158 °F	-
IP 67/NEMA 4	IP 67/NEMA 4	-
stainless steel 1.4305	stainless steel 1.4305	-
-	-	-
282/283	282/283	-
266/3	266/3	-

-25 °C/+70 °C	-25 °C/+70 °C	-
-13 °F/+158 °F	-13 °F/+158 °F	-
IP 67/NEMA 4	IP 67/NEMA 4	-
stainless steel 1.4401	stainless steel 1.4401	-
PVC 3x0.14	PVC 3x0.14	-
-	-	-
266/5	266/5	-

-	-25 °C/+70 °C	-
-	-13 °F/+158 °F	-
-	IP 67/NEMA 4	-
-	stainless steel 1.4401	-
-	PUR 3x0.14	-
-	-	-
-	266/5	-

