

KANALISATIES : ronde kanalen + flexibele buis

Gegalvaniseerd staal DX51D +275 MAC volgens norm EN 10246 2009
Klasse D



Spiraalbuis L 3m

Diameter 80mm
Diameter 100mm
Diameter 125mm
Diameter 150mm
Diameter 160mm
Diameter 200mm
Diameter 250mm
Diameter 315mm

ref. 309 L80
ref. 309 L100
ref. 309 L125
ref. 309 L150
ref. 309 L160
ref. 309 L200
ref. 309 L250
ref. 309 L315



Mof mannelijk

ref.309 MM80
ref.309 MM100
ref.309 MM125
ref.309 MM150
ref.309 MM160
ref.309 MM200
ref.309 MM250
ref.309 MM315



Mof vrouwelijk

ref.309 MV80
ref.309 MV100
ref.309 MV125
ref.309 MV150
ref.309 MV160
ref.309 MV200
ref.309 MV250
ref.309 MV315



T-stuk

ref. 309 T808080
ref. 309 T100100100
ref. 309 T125125125
ref. 309 T150150150
ref. 309 T160160160
ref. 309 T200200200
ref. 309 T250250250
ref. 309 T315315315



Bocht 90°

Diameter 80mm
Diameter 100mm
Diameter 125mm
Diameter 150mm
Diameter 160mm
Diameter 200mm
Diameter 250mm
Diameter 315mm

ref.309 B9080
ref.309 B90100
ref.309 B90125
ref.309 B90150
ref.309 B90160
ref.309 B90200
ref.309 B90250
ref.309 B90315



Bocht 45°

ref.309 B4580
ref.309 B45100
ref.309 B45125
ref.309 B45150
ref.309 B45160
ref.309 B45200
ref.309 B45250
ref.309 B45315



Bocht 60°

ref.309 B60125
ref.309 B60150
ref.309 B60160
ref.309 B60200
ref.309 B60250
ref.309 B60315



Bocht 30°

ref.309 B30125
ref.309 B30150
ref.309 B30160
ref.309 B30200
ref.309 B30250
ref.309 B30315



Ophangbeugel (10M)

Diameter 80mm
Diameter 100mm
Diameter 125mm
Diameter 150mm
Diameter 160mm
Diameter 200mm
Diameter 250mm
Diameter 315mm

ref. 309 OB80
ref. 309 OB100
ref. 309 OB125
ref. 309 OB150
ref. 309 OB160
ref. 309 OB200
ref. 309 OB250
ref. 309 OB315



Manuele regelklep

ref. 309 K80
ref. 309 K100
ref. 309 K125
ref. 309 K150
ref. 309 K160
ref. 309 K200
ref. 309 K250
ref. 309 K315



Zadelstuk

ref. 309 Z8080
ref. 309 Z100100
ref. 309 Z125125
ref. 309 Z150150
ref. 309 Z160160
ref. 309 Z200200
ref. 309 Z250250
ref. 309 Z315315



Zadelstuk plat

ref. 309 ZP80
ref. 309 ZP100
ref. 309 ZP125
ref. 309 ZP150
ref. 309 ZP160
ref. 309 ZP200
ref. 309 ZP250
ref. 309 ZP315



Eindstop

Diameter 80mm
Diameter 100mm
Diameter 125mm
Diameter 150mm
Diameter 160mm
Diameter 200mm
Diameter 250mm
Diameter 315mm

ref. 309 SM80
ref. 309 SM100
ref. 309 SM125
ref. 309 SM150
ref. 309 SM160
ref. 309 SM200
ref. 309 SM250
ref. 309 SM315



Spanbanden

ref. 309 C80
ref. 309 C100
ref. 309 C125
ref. 309 C150
ref. 309 C160
ref. 309 C200
ref. 309 C250
ref. 309 C315



Reducties

ref. 309 R160125
ref. 309 R200125
ref. 309 R200160

ref. 309 R250125
ref. 309 R250160
ref. 309 R250200

ref. 309 R315160
ref. 309 R315200
ref. 309 R315250

Flexibele kanalen



Aluminium flexibel luchtkanaal kl. M1
Temperatuurbereik -30°C / + 250°C
Lengte : 10m

ref. 309 FLEX80	Diameter 80mm
ref. 309 FLEX100	Diameter 100mm
ref. 309 FLEX125	Diameter 125mm
ref. 309 FLEX150	Diameter 150mm
ref. 309 FLEX160	Diameter 160mm
ref. 309 FLEX200	Diameter 200mm
ref. 309 FLEX250	Diameter 250mm
ref. 309 FLEX315	Diameter 315mm



Al / MWG / Al Aluminium flexibel geïsoleerd luchtkanaal kl. M1
Thermisch en akoestisch geïsoleerd met 25mm glaswol
Temperatuurbereik -30°C / +150°C
Lengte 10m

ref. 309 FLEXISO80	Diameter 80mm
ref. 309 FLEXISO100	Diameter 100mm
ref. 309 FLEXISO125	Diameter 125mm
ref. 309 FLEXISO150	Diameter 150mm
ref. 309 FLEXISO160	Diameter 160mm
ref. 309 FLEXISO200	Diameter 200mm
ref. 309 FLEXISO250	Diameter 250mm
ref. 309 FLEXISO315	Diameter 315mm