

BOCHT 90°	
met rubberen dichting	
Ø	Referentie
80	309 B9080
100	309 B90100
125	309 B90125
150	309 B90150
160	309 B90160
180	309 B90180
200	309 B90200
250	309 B90250
Segment-bocht met dichting	
225	309 BDS9225
250	309 BDS9250
315	309 BDS9315
355	309 BDS9355
400	309 BDS9400
450	309 BDS9450
500	309 BDS9500



geperste bocht, lineair gelast en gekalibeerd, met dubbele rubberen EPDM dichting

BOCHT 45°	
met rubberen dichting	
Ø	Referentie
80	309 B4580
100	309 B45100
125	309 B45125
150	309 B45150
160	309 B45160
180	309 B45180
200	309 B45200
250	309 B45250
Segment-bocht met dichting	
225	309 BDS4225
250	309 BDS4250
315	309 BDS4315
355	309 BDS4355
400	309 BDS4400
500	309 BDS4500



geperste bocht, lineair gelast en gekalibeerd, met dubbele rubberen EPDM dichting

Segment BOCHT 30°	
met rubberen dichting	
Ø	Referentie
125	309 B30125
150	309 B30150
160	309 B30160
180	309 B30180
200	309 B30200
250	309 B30250
315	309 B30315
355	309 B30355
400	309 B30400
450	309 B30450
500	309 B30500



geperste bocht, lineair gelast en gekalibeerd, met dubbele rubberen EPDM dichting

BOCHT 60°	
met rubberen dichting	
Ø	Referentie
125	309 B60125
150	309 B60150
160	309 B60160
180	309 B60180
200	309 B60200
250	309 B60250
315	309 B60315
355	309 B60355
400	309 B60400
450	309 B60450
500	309 B60500



geperste bocht, lineair gelast en gekalibeerd, met dubbele rubberen EPDM dichting