22MM PLASTIC ROUND INDICATOR: INDICATOR LIGHT WITH SMOOTH LENSE ILLUMINABLE Z=WITHOUT HOLDER RED Z= 50 UNITS PACKED

Design of the engrating machanism		
Design of the operating mechanism		indicator light
Material / of the activation element		plastic
Shape / of the activation element		Smooth lens
Number of switching positions		0
Product component / front ring		No
Product function / EMERGENCY STOP function		No
Holder:		
Material / of the holder		Plastic
waterial / of the holder		Plastic
General technical details:		
Resistance against shock		
• for devices with incandescent lamp / according to IEC 60068-2-		<= 30g
27		-
• for devices without incandescent lamp / according to IEC 60068- 2-27		<= 50g
Resistance against vibration / according to IEC 60068-2-6		20 200 Hz: 5g
Item designation		
according to DIN EN 61346-2		P
according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		Н
Tightening torque / of the screws in the bracket / maximum	N·m	1
Ambient temperature		
during operating	°C	-25 +70
during storage	°C	-40 +80
Protection class IP		IP66
climatic class / during the operating phase / according to EN 60721		3K6
Type of mounting		front mounting
Shape / of the installation hole		round
Installation width	mm	28
Mounting diameter	mm	22
	mm	11

Mounting depth mm 29

Certificates/ approvals:

General Product Approval

Declaration of Conformity

Test Certificates









Special Test Certificate

Shipping Approval











other

Confirmation

other

Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3SB3001-6AA20-ZB01X90/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3001-6AA20-ZB01X90

last change: Jan 21, 2013