










## Bascule



| Spécification  | Réf.     | UV.    | EUR/pièce HTVA | SP | EAN           |
|--|----------|--------|----------------|----|---------------|
|  blanc crème brillant | 0296 01  | 10     | 3,06           | 21 | 4010337296010 |
|  blanc brillant     | 0296 03  | 10     | 3,06           | 21 | 4010337296034 |
|  blanc satiné       | 0296 27  | 10/100 | 3,06           | 21 | 4010337296270 |
|  anthracite         | 0296 28  | 10     | 3,61           | 11 | 4010337296287 |
|  teinte alu         | 0296 26  | 10     | 6,04           | 11 | 4010337296263 |
|  noir mat           | 0296 005 | 10     | 6,04           | 11 | 4010337038061 |
|  gris mat           | 0296 015 | 10     | 6,04           | 11 | 4010337080220 |
|  acier inoxydable   | 0296 600 | 10     | 11,39          | 11 | 4010337021667 |
|  bronze             | 0296 603 | 10     | 11,86          | 11 | 4010337097747 |



laiton

0296 604

10

11,86

11

4010337097754



chrome

0296 605

10

11,86

11

4010337001416

## Indications

- En relation avec le set de joints et le cadre de finition (1x à 5x) des gammes d'interrupteurs standard 55 et Gira E22, on peut installer les interrupteurs et boutons-poussoirs à bascule protégés contre l'eau au degré de protection IP44 (ne s'applique pas aux bascule 2x).