


Item no.: 243-504  
 Product description: MICRO PUSH-WIRE CONNECTOR FOR JUNCTION BOXES  
 4-CONDUCTOR TERMINAL BLOCK



Produkt kann von Bild abweichen / product may differ

Packing unit 1000 10\*100 pieces

RoHS compliant

|                                  |                           |
|----------------------------------|---------------------------|
| Cross section [mm <sup>2</sup> ] | 0.6 - 0.8 mm <sup>2</sup> |
| Number of strands                | 4                         |
| Product group                    | 7 (Push Wire Conn.)       |
| pole count                       | 4                         |
| Cross section to [AWG]           | 20 AWG                    |
| Cross section [AWG]              | 22 - 0.6 mm               |
| Diameter to                      | 0.8 mm                    |
| Measured voltage EN              | 100 V                     |
| Measured shock voltage           | 1.5 kV                    |
| Pollution degree                 | 2                         |
| Current intensity EN             | 6 A                       |
| Weight                           | 0.76 g                    |
| Color                            | yellow                    |
| Wiring type                      | Side-entry                |
| No. of connection Points         | 4                         |
| No. of potentials                | 1                         |
| Height                           | 6.8 mm                    |
| Height                           | 0.268 in                  |
| Width                            | 10 mm                     |

|       |          |
|-------|----------|
| Width | 0.394 in |
| Depth | 10 mm    |
| Depth | 0.394 in |



|                   |         |
|-------------------|---------|
| Strip length from | 5 mm    |
| Strip length to   | 6 mm    |
| Strip length      | 0.22 in |



| Item no. | Admission office | Approval no.      | Voltage [V] | Current [A] | Cross section [ mm <sup>2</sup> ] |
|----------|------------------|-------------------|-------------|-------------|-----------------------------------|
| 243-504  | ABS              | 04-HG476172/1-PDA | 100         | 6           | 0,5-0,75                          |
| 243-504  | CSA              | 18677-31          | 150         | 7           | 22-20                             |
| 243-504  | KEMA             | 2123448.01        | 100         | 6           | 05-1,0 sol                        |
| 243-504  | LR               | 04/20013(E3)      | 100         | 6           | 0,5-0,75                          |
| 243-504  | RMR              | 11130002          | 100         | 6           | 0,5-0,75                          |
| 243-504  | UR               | E45172            | 150         | 7           | 22-18                             |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected