

Product data sheet

Item No. 92.232.1000.1

Cable assembly GST18I3K1BS 15 10SW

geis® Extension cable female - male; length: 1m; type GST18I3;
3-pole; 250 V / 16 A; colour of coding: black with black strain-relief;
cable: H05VV-F 3G1,5, colour: black



Item No.	92.232.1000.1
EAN	4015573319851
Order Unit	75 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Technical drawing

Kabel/cable H05VV-F3G1,5
Farbe/colour: siehe Tabelle/see table

Weitere Daten siehe Katalog
further data see catalog

.F	Farbe colour	Codierung Buchse female *X*	Codierung Stecker male *Y*	Kabelfarbe cable colour
.1	schwarz black	N ⊕ L	L ⊕ N	schwarz black
.2	weiß white	N ⊕ L	L ⊕ N	weiß white
.3	grau grey	N ⊕ L	L ⊕ N	schwarz black
.5	rot red	N ⊕ L	L ⊕ N	schwarz black

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Typ/type: GST18i3K1BS 15

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) exampel (colour: black)	Typ type
92.232.XX00.F	XX in dm-Schritten	92.232.1000.1 = 10dm/L= 1000mm	GST18i3K1BS 15 10SW
U2.232.XX00.F	XX in m-Schritten	U2.232.1200.1 = 12 m/L=12000mm	GST18i3K1BS 15 X12SW
92.232.XX90.F	XX in dm-Schritten	92.232.1090.1 = 10dm/L= 1000mm	

90.F = spezielle Verpackung und Etikettierung nach A 1960.000
special packaging and lable according to A 1960.000

Tolerancing Size ISO 14269 Telecommunication system Size ISO 14269. This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances. (This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.)

Zeichnung: keine revisionen zulässig	Übertrag: -	Blatt: 1 von 1
General tolerance: GD - drawing, no manual modifications allowed	Viewing: -	Sheet: 1 of 1

Werkstoff/Material	2.006	Tag/Dat.	Name	Zeichnung Nr./Drawing No.	Index
Abmaß/Sizes	20.01	08.06.11	Stück 1	T	92.232.0200.1 01K a
Note in mm/Dimensions are in mm					

PRE-ASSEMBLED CABLE
KONFEKT-LEITUNG
Buchse/female - Stecker/male 1,5mm
Cr impausführung/crimpersion K1 250V