



## Product data sheet

Item No. 92.932.3053.1

Male connector with strain relief GST18I3S S1 ZR1 SW

Connector GST18i3, 3 pole, male, screw connection, 250 V, 20 A, colour of coding: black, colour of housing: black



Item No.	92.932.3053.1
EAN	4015573721876
Order Unit	50 Piece(s)

## Certificates / Approvals







## Technical data

General	
Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

### **Connection Data**

Cable diameter	10.5 mm
Cable diameter 2	6.5 mm
Connection cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.75 mm²
Connection cross section stranded max.	2.5 mm <sup>2</sup>
Cross section stranded 2	0.75 mm²





Terminations per pole	1
Model	
Model	male
Connection type	Screw connection
Degree of protection (IP)	IP20
Material	
Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Tin-plated
Dimensions	
Length	69.4 mm
Width	28.2 mm
Height	12.6 mm

# Technical drawing

