

M6/8

General Information

| | |
|------------------------|---------------------|
| Extended Product Type: | M6/8 |
| Product ID: | 1SNA115118R1100 |
| EAN: | 3472591151183 |
| Catalog Description: | M6/8 |
| Long Description: | Blocs Liaison Vissé |

Les blocs de liaison Vissé ABB Entrelec permettent le raccordement électrique de deux ou plus conducteurs sur le même support mécanique, clipsable sur profilé DIN.

Application:

tout circuit électrique monté en armoire ou coffret

Avantages:

Gamme très étendue
Cette fonction est également disponible dans les autres technologies de raccordement:
Ressort et ADO (auto-dénudant).
Montage sur multi-profilé DIN 1, 2 ou 3

Caractéristiques
Intensité de 24A à 415A
Plage de raccordement de 2.5mm² à 240mm²
Conforme à la norme IEC 60947-7-1

Categories

Products » Produits basse tension » Raccordement » Blocs de jonction » Blocs de jonction vissés

Ordering

| | |
|-------------------------|---------------|
| EAN: | 3472591151183 |
| Minimum Order Quantity: | 50 piece |
| Customs Tariff Number: | 85369010 |

Dimensions

| | |
|---------------------|------|
| Product Net Weight: | 13 g |
|---------------------|------|

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 50 piece |
| Package Level 1 Width: | 81 mm |
| Package Level 1 Height: | 47 mm |
| Package Level 1 Length: | 220 mm |
| Package Level 1 Gross Weight: | 0.65 kg |
| Package Level 1 EAN: | 3472591151183 |
| Package Level 2 Units: | 1500 piece |
| Package Level 2 Width: | 300 mm |
| Package Level 2 Height: | 300 mm |
| Package Level 2 Length: | 500 mm |
| Package Level 2 Gross Weight: | 20 kg |
| Product Packing Type: | Box |

Environmental

| | |
|--------------|---|
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|--------------|---|

Technical UL/CSA

| | |
|---------------------------------|----|
| Flammability According to UL94: | V0 |
|---------------------------------|----|

Additional Information

| | |
|--|-------------------------------|
| Color: | gris |
| Connection Type: | Screw clamp |
| Dielectric Test Voltage: | 3500 V |
| Function: | Liaison |
| Gauge(s) of Form: | A5 |
| IIT Publishing Status: | Level 0 - Information enabled |
| Degré de pollution: | 2 |
| Product Main Type: | M6/8 |
| Product Name: | Terminal block |
| Tension assignée de tenue aux chocs (U _{imp}): | 8 kV |

| | |
|----------------------------------|--|
| Recommended Screw Driver: | 4 mm |
| Spacing: | 8 mm |
| Sub-Function: | Simple étage |
| Tightening Torques: | acc. IEC 60947-1 0.8 N·m Manufacturer 1 N·m |
| Wire Stripping Length: | 12 mm |

Certificates and Declarations (Document Number)

| | |
|--|---------------------------------|
| Declaration of Conformity - CE: | 1SND225001C1000 |
| GOST Certificate: | 1SND161005A1103 |

Classifications

| | |
|------------------------------------|----------|
| E-nummer: | E2925510 |
| Object Classification Code: | X |