



SIMATIC DP,BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 90 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITH PG SOCKET 15,8 X 59 X 35,6 MM (WXHxD),

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

**Interfaces**

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection

- for network components and terminal equipment

9-pin Sub-D plug

Design of the electrical connection / FastConnect

Yes

**Mechanical data**

Material / of the enclosure

plastic

**Design, dimensions and weight**

Width

15.8 mm

Height

59 mm

Depth

35.6 mm

Net weight

10 g

**Permitted ambient conditions**

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-40 ... +70 °C

-40 ... +70 °C

Relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operating / maximum</li> </ul>	95 %
Protection class IP	IP20
<b>Product properties, functions, components / general</b>	
Product feature / [not supplied - silicon-free]	Yes
Product component	
<ul style="list-style-type: none"> <li>• PG connection socket</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• strain relief</li> </ul>	Yes
<b>Standards, specifications, approvals</b>	
Verification of suitability	
<ul style="list-style-type: none"> <li>• RoHS conformity</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• UL-registration</li> </ul>	Yes
<b>letzte Änderung:</b>	Oct 24, 2012