



SIMATIC DP,
 ET 200M INTERFACE IM 153-4 PN IO FOR MAX. 12 S7-
 300 MODULES,
 EXTENDED FUNCTIONS: ISOCHRONEOUS REALTIME
 COMMUNICATION CLASS 1 AND 2,
 MODULE EXCHANGE W/O PG,
 OPERATION W/O MMC,
 MAINTENANCE NEW IO MODULES ARE SUPPORTED

General information

Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0302H

Supply voltage

24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
permissible range (ripple included), lower limit (DC)	20.4 V
permissible range (ripple included), upper limit (DC)	28.8 V
External protection for supply cables (recommendation)	In a construction with grounded reference potential, a fuse is necessary for redundant interface modules (Recommendation: 2.5 A)

Mains buffering

Mains/voltage failure stored energy time	5 ms
---	------

Input current

Current consumption, max.	600 mA
Inrush current, typ.	4 A
I²t	0.09 A ² ·s

Output voltage

Rated value, 5 V DC	Yes
Output current	
for backplane bus (5 V DC), max.	1.5 A
Power losses	
Power loss, typ.	6 W ; Typical
Address area	
Addressing volume	
Inputs	192 byte
Outputs	192 byte
Hardware configuration	
Number of modules per DP slave interface, max.	12
Communication functions	
Bus protocol/transmission protocol	PN IO
Interrupts/diagnostics/status information	
Diagnostics indication LED	
Connection to network LINK (green)	Yes
Transmit/receive RX/TX (yellow)	Yes
Isolation	
Isolation checked with	500 V DC
Degree and class of protection	
IP20	Yes
Ambient conditions	
Operating temperature	
Min.	0 °C
max.	60 °C
Air pressure	
Operating altitude above sea level, max.	2000 m
Dimensions	
Width	40 mm
Height	125 mm
Depth	118 mm
Weight	
Weight, approx.	215 g ; approx.
Status	Jul 22, 2013