6ES7232-4HA30-0XB0 Page 1

SIEMENS

Product data sheet 6ES7232-4HA30-0XB0



SIMATIC S7-1200, ANALOG OUTPUT SB 1232, 1 AO, +/- 10VDC (12 BIT RES.) OR 0 - 20 MA (11 BIT RES)

Input current	
from backplane bus 5 V DC, typ.	15 mA
Output voltage	
Power supply to the transmitters	
Supply current, max.	25 mA
Power losses	
Power loss, typ.	1.5 W
Analog outputs	
Number of analog outputs	1
Cycle time (all channels) max.	Voltage: 300 μ S (R), 750 μ S (1 uF) Current: 600 ms (1 mH); 2 ms (10 mH)
Output ranges, voltage	
-10 to +10 V	Yes
Output ranges, current	
0 to 20 mA	Yes
Load impedance (in rated range of output)	

6ES7232-4HA30-0XB0 Page 2

with voltage outputs, min.	1000 Ω	
with current outputs, max.	- 600 Ω	
Cable length		
Cable length, shielded, max.	10 m ; Shielded, twisted wire pair	
Analog value creation		
Measurement principle	Differential	
Integrations and conversion time/ resolution per channel		
Resolution (incl. overrange)	V/12 bits, I/11 bits	
Smoothing of measured values		
Parameterizable	Yes	
Errors/accuracies		
Temperature error (relative to output area)	25°C ±0.5% bis 55°C ±1%	
Interrupts/diagnostics/status information		
Alarms		
Alarms	Yes	
Diagnostic messages		
Diagnostic functions	Yes	
Diagnostics indication LED		
For status of the outputs	Yes	
Degree and class of protection		
IP20	Yes	
Standards, approvals, certificates		
CE mark	Yes	
C-TICK	Yes	
FM approval	Yes	
Climatic and mechanical conditions for storage and transport		
Climatic conditions for storage and transport		
Free fall		
Drop height, max. (in packaging)	0.3 m ; five times, in dispatch package	
Temperature		
Permissible temperature range	-40 °C to +70 °C	
Air pressure acc. to IEC 60068-2-13		
Permissible air pressure	1080 to 660 hPa	

6ES7232-4HA30-0XB0 Page 3

Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Permissible temperature range	0 °C to 55 °C horizontal installation 0 °C to 45 °C vertical installation
Pollutant concentrations	
SO2 at RH < 60% without condensation	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
Mechanics/material	
Type of housing (front)	
Plastic	Yes
Dimensions	
Width	38 mm
Height	62 mm
Depth	21 mm
Weight	
Weight, approx.	40 g
Status	Sep 24, 2012