

## F CONNECTOR



EX59-39/79

Article number 695020304

PRODUCT CATEGORY: CATV

STATUS: AVAILABLE



### Product

F CONNECTOR  
EX59-39/79

Ultra high quality F type compression connector, for cable with 6 mm diameter (like RG 59). Every day installers are faced with identifying old unmarked cable and having to guess which connector is correct. The wrong connector choice degrades the plant, leading to noise and moisture ingress that ultimately results in a service call. The EX59-39/79 takes the guesswork out of matching connector to cable—and reduces service calls.

### Properties

5 Year  
Warranty

Class A-  
Screening

High  
Durability

Low  
Loss

### Certificates



### Included

N/A

### Tools

- 1 piece Compression tool VT 300  
Article number 695020315



### Instruction video

[www.hirschmann-multimedia.net/  
montagefilm](http://www.hirschmann-multimedia.net/montagefilm)

### Instruction card

[www.hirschmann-multimedia.net/  
installation/installatie-schema](http://www.hirschmann-multimedia.net/installation/installatie-schema)

## Mechanical Specifications

Dimensions hwxwd  
29 x 11 x 11 mm

Weight  
0.007 kg

Color  
Metallic

## PRODUCTSHEET

### EX59-39/79

### F CONNECTOR

## Specifications

### Electrical

	specification	standard
Frequency range	5-2200 MHz	
Impedance	75 Ω nominal	
Return loss	> 39 dB 5-500 MHz	IEC 61169-1, 9.2.1.4
	> 36 dB 500-860 MHz	IEC 61169-1, 9.2.1.4
	> 34 dB 860-1006 MHz	IEC 61169-1, 9.2.1.4
	> 29 dB 1006-1750 MHz	IEC 61169-1, 9.2.1.4
Insertion loss	< -0.1 dB	
Amp rating	2 A	
Shielding	class A+	EN 50117
Dielectric strength	> 2 KV	IEC 61169-1, 9.2.5
Isolation resistance	> 29.99 GΩ @ 500 V DC	IEC 61169-1, 9.2.5
CPD	< -110 dBC	ANSI/SCTE 109 2005

### Environmental

Temperature range operating	-40°C to +80°C	
Temperature range installation	-5°C to +50°C	
Sealing test	IPX8 - 1meter/24 hours	IEC 60529
Corrosion protection		ASTM B 117-94


### Mechanical

Interface	F	IEC 61169-24
Pull strength	> 20 kgf	ANSI/SCTE 99
Approved compression tool	VT150DK - VT300 - CAT-AS-EX - EX59/6 CAT CAT-AS-IEC/F-FX - CATAIO PLUNGER 1 & 2	

### Material and finish

Housing	NiSn (NITIN) plated brass	ASTM B605
O'ring	EPDM	

## Wiring diagram



Fold braiding back

## Related product - EX6-51WSNT

Article number 695020307



## Related product - EX6-5183

Article number 695020335



## Related product - KOKA 799 WHITE

Article number 198799101



## Contact

🏠 Pampuslaan 170  
1382 JS WEESP

✉ info@hirschmann.nl

☎ NL 31 (0)294 46 25 55  
BE 32 (0)2 46 13 095

🌐 [www.linkedin.com/company/hirschmann-multimedia-b.v.](http://www.linkedin.com/company/hirschmann-multimedia-b.v)

📘 [www.facebook.com/hirschmann.multimedia](http://www.facebook.com/hirschmann.multimedia)

📺 [www.youtube.com/HirschmannMultimedia](http://www.youtube.com/HirschmannMultimedia)

## Hirschmann Multimedia B.V.

Hirschmann Multimedia B.V. is an international knowledge company and manufacturer, located in Weesp - The Netherlands. Hirschmann Multimedia focusses on leading the market by being innovative, flexible and renewing.

### Hirschmann Multimedia Products (HMP):

Serving the retail and installer market, Hirschmann Multimedia Products is expanding from The Netherlands and Belgium towards 16 other European countries as of 2014. Through a qualified and selected dealer and installer network, HMP provides in products for COAX, IP and satellite systems.

Productsheet EX59-39/79

Article number 695020304

Version 11.2014-1.0

Page 2 / 2