

PRODUCT-DETAILS

6583-500

6583-500 Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI)



Informations générales

Extension du type de produit	6583-500
Code de produit	2CKA006590A0178
EAN	4011395066928
Description courte	6583-500 Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI)
Description longue	<p>Universal Central Dimmer modular. For switching and dimming of incandescent lamps, 230 V halogen incadescent lamps and low-voltage halogen lamps with conventional or electronic transformers. With light-level memory, adjustable minimum brightness and with intelligence for universal operation. Capacity expansion via output-side parallel-connected load line (with RJ 12 plug) with a power module 6584 (max. 6 pcs = 3000 W/VA total wattage). Compatible with control module 6597 and ABB Powernet KNX in combination with control module 6997/60. Operation using a plug-in push switch/rotary and timer control cover 6543/10, ..11, --12 and/or a conventional push switch (2020 US or 2021/6 UK or Rotary Dimmer insert for combination with flush-mounted inserts 6592 U. Low-noise, short-circuit-proof, overload-protected.</p>

Technique

Adapté pour	2CKA006590A0179 2CKA006590A0155 2CKA006590A0181 2CKA006590A0183 2CKA006590A0185 2CKA006198A0102 2CKA006900A1659 2CKA001413A0475 2CKA001413A0897
Tension nominale (U_r)	230 V
Rated Control Supply Voltage (U_s)	220...240 V

Auxiliary Voltage AC/DC	230 V AC/DC
Fréquence (f)	50...60 Hz
Fréquence assignée (f)	50...60 Hz
Puissance Watt	60...500 V·A
Product Range	Busch-Dimmer®
Type de raccordement	Screw Clamp
Type de charge	Universal
Type de montage	Mounted Din Rail Component
Type of Fastening	Mounting with Claw
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Material quality: Thermoplastic (3) Material: Plastic (3)
RAL Number	RAL 7035 - Gris clair
Poids de la batterie	0 g
Nombre de batteries	0

Environnement

Température de l'air ambiant	Operation 0 ... +45 °C
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Dimensions

Width in Number of Modular Spacings	2
Poids net	0.123 kg

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Largeur	92 mm
Emballage Niveau 1 Hauteur	58 mm
Emballage Niveau 1 Longueur	78 mm
Emballage Niveau 1 Poids	0.188 kg
Emballage Niveau 1 EAN	4011395066928
Emballage Niveau 2 Unités	10 pièce
Emballage Niveau 2 Largeur	168 mm
Emballage Niveau 2 Hauteur	112 mm
Emballage Niveau 2 Longueur	298 mm
Emballage Niveau 2 Poids	2.005 kg

Commande

Quantité minimum	1 pièce
Code douanier	85365080
E-Number (Sweden)	1360020

ID Produit de
remplacement
(NOUVEAU)

2CKA006590A0193

Pays d'origine

Germany (DE)

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1696
Instructions et manuels	DEBJE-6583-6584_ABB_OA_2012-12-17_DE_R01
REACH Declaration	2CKA309999E9999
Informations RoHS	9AKK104295D8727

Popular Downloads

Instructions et manuels	DEBJE-6583-6584_ABB_OA_2012-12-17_DE_R01
-------------------------	--

Classifications

ETIM 7	EC000025 - Dimmer
ETIM 8	EC000025 - Dimmer
Arborescence du catalogue EPLAN	Electrical engineering / Sensor, switch, and pushbutton / Switch , pushbutton
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144014

Catégories

Produits basse tension → Switch Assortments → Light / LoadControl → Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI)
→ Rotary Dimmer - DIN Rail



