

Date

Name

Client

Project Name



Quote#

Type/Quantity

CIRCLE S Hi S2

202 01 4010

[Weblink](#)



Cutout shape/size: 82 mm

Recessed depth: 70 mm

Available colors: ALUMINIUM (202 01 4010 ALU)
WHITE (202 01 4010 W)

ADJUSTABLE 0°- 30° / 350°
MAINS DIMMING - TRAILING EDGE

GU10 // 100-240V / 50-60Hz
 1 x QPAR51 max.50W

Class: II

Weight: 0.2 KG
Protection level: IP20
Minimum distance: 0,5m


Remarks: WHITE finish : max. 35W

Options: TRANSFO


For detailed installation instructions, please consult the manual. [202_11_4010_HAND.pdf](#)

CIRCLE S Hi S2
202 01 4010


Ceiling compatibility




Concrete



Concrete + plaster



Hollow-core slab




Hollow-core slab + plaster

CIRCLE S Hi S2
202 01 4010

Related references


CONTROL GEAR, BALLAST AND TRANSFORMERS

[Weblink / Specsheet](#)



TRANSFO 100W
200 46 10
220-240V / 50-60Hz

[Weblink / Specsheet](#)



TRANSFO 50W
200 46 06
220-240V / 50-60Hz