

RONDE aftakkingen (zadelstuk)	
met rubberen dichting	
Ø	Referentie
080/080	309 Z8080
090-100/080	309 Z10080
112-125/080	309 Z12580
140-160/080	309 Z15080 309 Z16080
180-224/080	309 Z20080
250-315/080	309 Z25080 309 Z31580
100/100	309 Z100100
112-125/100	309 Z125100
140-160/100	309 Z150100 309 Z160100
180-224/100	309 Z200100
250-315/100	309 Z250100 309 Z315100
355-500/100	309 Z355100 309 Z500100
125/125	309 Z125125
140-160/125	309 Z150125 309 Z160125
180-224/125	309 Z200125
250-315/125	309 Z250125 309 Z315125
355-450/125	309 Z355125
150/150	309 Z150150
180-224/150	309 Z200150
160-160	309 Z160160
180-224/160	309 Z200160
250/160	309 Z250160
315-355/160	309 Z315160 Z355160
400-450/160	309 Z400160
200/200	309 Z200200
250/200	309 Z250200
315-355/200	309 Z315200 309 Z355200
400-450/200	309 Z400200
250/250	309 Z250250
315/250	309 Z315250
355/250	309 Z355250
400-450/250	309 Z400250
315/315	309 Z315315
400/315	309 Z400315




Geperst gestroomlijnde aftakkingen met dubbele rubberen EPDM dichting

Aftakkingen



PLATTE aftakkingen (zadelstuk)	
met rubberen dichting	
Ø	Referentie
80	309 ZP80
100	309 ZP100
125	309 ZP125
150	309 ZP150
160	309 ZP160
180	309 ZP180
200	309 ZP200
250	309 ZP250
315	309 ZP315
355	309 ZP355
400	309 ZP400
450	309 ZP450
500	309 ZP500

A photograph of a grey, flanged metal fitting, likely made of stainless steel, with a double rubber seal. The fitting is shown from a slightly elevated perspective, highlighting its circular shape and the raised flange on top.

Geperst gestroomlijnde aftakkingen met dubbele rubberen EPDM dichting