




Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth, PL6 7TL, England.  
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724  
 and at 1, Enterprise Close, Factory Lane, Croydon, CR0 3RZ  
 Telephone 020 8665 8100 Fax 0208 8665 8100  
 Website: <http://www.birchvalley.co.uk> E mail: [info@birchvalley.co.uk](mailto:info@birchvalley.co.uk)



## GREEN/YELLOW P.V.C EARTH SLEEVING

*GY is a P.V.C. sleeving supplied with green and yellow stripes for use in earth identification. In addition to direct use this sleeving is widely sold in the distribution market and for electrical contracting purpose.*

### MATERIAL CHARACTERISTICS

Continuous temperature	-20 to 70 C	
Insulation resistance	10 <sup>11</sup> Ohm/cm	
Dielectric strength	20 kV/mm	IEC 243
Tensile strength	15 MPa	ISO 37
Elongation at break	220%	ISO 37
Hardness	BSS20-30	
Flammability	self extinguishing in 30 seconds	
Specification	BS2848/3/85T except wall thickness	
RoHS compliant	yes	

### TEST METHODS

Part no.	Inside dia. mm	Nominal wall mm	Coil size m
GY 1.5	1.5	0.4	100
GY 2	2.0	0.4	100
GY 3	3.0	0.4	100
GY 4	4.0	0.4	100
GY 5	5.0	0.45	100
GY 6	6.0	0.45	100
GY 8	8.0	0.45	100
GY 10	10.0	0.45	100
GY 12	12.0	0.45	100
GY 14	14.0	0.45	100
GY 16	16.0	0.45	100
GY 18	18.0	0.45	100
GY 19	19.0	0.45	100
GY 20	20.0	0.45	100
GY 25	25.0	0.45	100

Can be supplied on reels to special order

All sizes available in cut lengths.

Standard colour -green/yellow only.

Larger sizes may be subject to minimum quantities.