












		
Reference	12403630		
Dimensions (LxWxH)	103x67x21		
Input	220-240V 50/60Hz		
Ambient temperature	-25°C to +50°C		
Power factor (max)	0.98		
Dimming	1-10V/PUSH DIM (push dim: optional sync cable 12400100)		
Max drivers on MCB 16A type B	15		
Output	350mA / 15W 1-43V DC	500mA / 22W 1-43V DC	700mA / 25W 1-36V DC
DIP-switch setting			
Cake 48 IP55 LED GE	14 	14 	
Chapeau 206 LED GE	2	2	1
Duell recessed 1x LED GE	2	2	
Duell recessed 2x LED GE	1	1	
Ex-L low 158 LED GE	1	1	
Grib LED GE	4		
Hipy 110 IP67 LED GE	2 	2 	1 
Hipy 70 IP67 LED GE	4 		
Intro 89 IP44 GE	2	2	
Julien IP54 LED GE	4		
K-0 80 LED GE	2	2	
K-1 89 LED GE	2	2	
Kurk IP40 LED GE	2	2	1
Kurk surface IP40 LED GE	2	2	1
Lotis 48 IP55 LED GE	14 	14 	
Lotis 82 IP55 LED GE	2	2	
Lotis 82 LED GE	2	2	
Lotis 97 adjustable LED GE	2	2	
Marty LED GE	14 		
Mini a(r)mor LED GE	14 		
Mini multiple 1x LED GE	2	2	
Mini multiple 2x LED GE	1	1	
Mini multiple 3x LED GE			
Mini multiple 4x LED GE			
M-LED 111 GE	1	1	1
Nomad 2x LED GE	1	1	
Nomad 4x LED GE			
Rektor recessed LED GE	1	1	
Scotty 270 adjustable LED GE	1		
Scotty 270 LED GE	1	1	
Slide square clockwork LED GE	2	2	
Slide square IP44 LED GE	2	2	
Slide square LED GE	2	2	
Slide twin LED GE	1	1	
Smart cake 115 adjustable LED GE	2	2	
Smart cake 115 LED GE	1	1	1
Smart cake 82 LED GE	2	2	
Smart kup 115 adjustable LED GE	2	2	
Smart kup 115 LED GE	1	1	1
Smart kup 82 LED GE	2	2	
Smart lotis 115 adjustable LED GE	2	2	
Smart lotis 115 LED GE	1	1	1
Smart lotis 82 LED GE	2	2	
Stove LED GE	2	2	1
Thub metal 120 LED GE	2	2	

 driver does not fit through cutout hole of fixture