


Reference	12403830		
Dimensions (LxWxH)	111x52x22		
Input	220-240V 50/60Hz		
Ambient temperature	-25°C to +50°C		
Power factor (max)	0.95		
Dimming	1-10V/PUSH DIM (push dim: optional sync cable 12400100)		
Max drivers on MCB 16A type B	50		
Output	350mA / 15W 1-43V DC	500mA / 20W 1-43V DC	
DIP-switch setting			
Cake 48 IP55 LED GE	14	△	13
Chapeau 206 LED GE	2		1
Duell recessed 1x LED GE	2		1
Duell recessed 2x LED GE	1		
Ex-L low 158 LED GE	1		1
Grib LED GE	4		
Hipy 110 IP67 LED GE	2	△	1
Hipy 70 IP67 LED GE	4	△	
Intro 89 IP44 GE	2		1
Julien IP54 LED GE	4		
K-0 80 LED GE	2	△	1
K-1 89 LED GE	2	△	1
Kurk IP40 LED GE	2		1
Kurk surface IP40 LED GE	2		1
Lotis 48 IP55 LED GE	14	△	13
Lotis 82 IP55 LED GE	2		1
Lotis 82 LED GE	2		1
Lotis 97 adjustable LED GE	2		1
Marty LED GE	14	△	
Mini a(r)mor LED GE	14	△	
Mini multiple 1x LED GE	2		1
Mini multiple 2x LED GE	1		
Mini multiple 3x LED GE			
Mini multiple 4x LED GE			
M-LED 111 GE			1
Nomad 2x LED GE	1		
Nomad 4x LED GE			
Rektor recessed LED GE	2		1
Scotty 270 adjustable LED GE			
Scotty 270 LED GE			
Slide square clockwork LED GE	2		1
Slide square IP44 LED GE	2		1
Slide square LED GE	2		1
Slide twin LED GE	1		
Smart cake 115 adjustable LED GE	2		1
Smart cake 115 LED GE	1		1
Smart cake 82 LED GE	2		1
Smart kup 115 adjustable LED GE	2		1
Smart kup 115 LED GE	1		1
Smart kup 82 LED GE	2		1
Smart lotis 115 adjustable LED GE	2		1
Smart lotis 115 LED GE	1		1
Smart lotis 82 LED GE	2		1
Stove LED GE	2		1
Thub metal 120 LED GE	2		1

△ driver does not fit through cutout hole of fixture