

Date

Name

Client

Project Name



Quote#

Type/Quantity

**MINIGRID IN TRIMLESS 1 FRAME + MINIGRID
SNAP-IN SOFT**

202 73 01 + 202 790 81120

[Weblink](#)



Opening formaat:	KIT mm
Inbouwdiepte:	85 mm
Beschikbare kleuren:	ZWART + ZWART (202 73 01 B + 202 790 81120 B) WIT + WIT (202 73 01 W + 202 790 81120 W) ZWART + WIT (202 73 01 B + 202 790 81120 W) WIT + ZWART (202 73 01 W + 202 790 81120 B)

ADJUSTABLE 0° - 20°/350°
INCL.1 x POWERLED WHITE 10W / CRI>80 / 2700-1800K /850 lm
INCL.1 x REFLECTOR FL-33°
EXCL. DIMMABLE LED POWER SUPPLY 650mA-DC

LED Technics:	Lichtbron: 850 lm // 10 W // 85 lm/W Luminaire: 536 lm // 12 W // 47 lm/W
---------------	--

Klasse:	III
Gewicht:	0.5 KG
Protection level:	IP23/20
Minimumafstand:	n.v.t.

Opmerkingen:	Parts to be ordered seperately.
Benodigdheden:	DIMMABLE LED POWER SUPPLY 650mA-DC MINIGRID IN 1 MOUNTING KIT MINIGRID IN 1 MOUNTING KIT LARGE CONCRETE PACK MGIT 1

Voor gedetailleerde installatie-instructies, raadpleeg de handleiding. [202_73_01_HAND.pdf](#)


MINIGRID IN TRIMLESS 1 FRAME + MINIGRID SNAP-IN SOFT

202 73 01 + 202 790 81120

Related references

LED VOEDINGEN

[Weblink / Specificatieblad](#)




LED POWER SUPPLY
650mA-DC DIM8
300 90 915 ED8
220-240V / 50-60Hz
Aantal toestellen: 1

Related references

BETON DOOS VOOR ZICHTBETON

[Weblink /
Specificatieblad](#)




CONCRETE PACK MGIT 1
202 71 96 01

Related references

MONTAGE KIT

[Weblink /
Specificatieblad](#)



MINIGRID IN 1 MOUNTING
KIT
202 71 95 01

[Weblink /
Specificatieblad](#)



MINIGRID IN 1 MOUNTING
KIT LARGE
202 71 95 01L

