




LUNA ROUND IP44

CEILING RECESSED



1.0 LED HV

LED 7W | 220-240VAC
PCB 3-step | incl. PS | phase-cut dim
aluminium | stainless steel
opal cover | polyamide | PMMA

0.18kg | IP44 | 2-25

76 | 50 | 2-25


3000K | >90 CRI | 350lm

CODE	CODE
114388W5	114388M5
114388B5	

OPTIONAL

dimmer	CODE
for switch	90019017
for din rail	90019018

more specs on page 591



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium | stainless steel
opal glass | polyamide

0.19kg | IP44 | 2-25

80 | 100 | 2-25

CODE	CODE
114381W	114381M
114381B	

Light Colour Selection

LUMEN CRI	CODE
2700K 370/500 >90	3
3000K 390/520 >90	5
1800-2850K 16V 230/320 >95	9


ALWAYS USE

power supply	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 588

OPTIONAL

recessed housing	CODE
recessed housing	90012026
plasterkit	90017101



1.0 PAR16

PAR16 max.10W | GU10
100-240VAC | 50-60Hz
aluminium | stainless steel
opal glass | polyamide

0.24kg | IP44 | 2-25

80 | 120 | 2-25

CODE	CODE
114120W0	114120M0
114120B0	


OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

CODE	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 593

recessed housing	CODE
recessed housing	90012026
plasterkit	90017101



1.0 MR16

QR-CBC51 max.10W | GU5.3
12V | excl. power supply
aluminium | stainless steel
opal glass | polyamide

0.28kg | IP44 | 2-25

80 | 100 | 2-25

CODE	CODE
114110W0	114110M0
114110B0	

ALWAYS USE

power supply

CODE	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 591

OPTIONAL

recessed housing	CODE
recessed housing	90012026
plasterkit	90017101