



BE GY20 E VU 9G1,5 Std+ZRZWWOR R1

P. 20mm+H07V-U Eca 9G1.5 G/Y BL BR BLA GR B/R B/W WH OR C100

Properties of the article

◦ Articulenumber	1234000435
◦ Barcode	5420056252010
◦ Category	Energy & Light
◦ Gross weight (kg)	24.6
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	H07V-U 9G1.5
	
◦ Color	
◦ Insulation	PVC
◦ CPR Class	eca

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	IEC 60227-1; EN 50575:2014+A1:2016

Certificates

