

automaten DX 6 - 10 kA

curve C



063 74

064 68

064 88

065 66

Technische kenmerken (blz. 680 tot 685)
 Afmetingen (blz. 705) - Goedkeuringen CEBEC (blz. 828)

Onderbrekingsvermogen:

- 6 volgens NBN C 61-898 - 400 V
- 10 kA volgens IEC 60947-2 - 400 V

Verp.	Ref.	Eenpolig 230/400 V~			
		Nominale stroomst. (A)	Onderbrekingsvermogen NBN C 61-898 230 V	Onderbrekingsvermogen IEC 60947-2 (kA) 230 V	Aantal modules van 17,5 mm
1	063 68	1	6	10	1
1	063 69	2	6	10	1
1	063 70	3	6	10	1
1	063 71	4	6	10	1
1	063 72	6	6	10	1
10	063 74	10	6	10	1
10	063 76	16	6	10	1
1	063 77	20	6	10	1
1	063 78	25	6	10	1
1	063 79	32	6	10	1
1	063 80	40	6	10	1
1	063 81	50	6	10	1
1	063 82	63	6	10	1

Verp.	Ref.	Driepolig 400 V~				
		Nominale stroomst. (A)	Onderbrekingsvermogen NBN C 61-898 400 V	Onderbrekingsvermogen IEC 60947-2 (kA) 400 V	Onderbrekingsvermogen IEC 60947-2 (kA) 230 V	Aantal modules van 17,5 mm
1	064 80	1	6	10	25	3
1	064 81	2	6	10	25	3
1	064 82	3	6	10	25	3
1	064 83	4	6	10	25	3
1	064 84	6	6	10	25	3
1	064 86	10	6	10	25	3
1	064 88	16	6	10	25	3
1	064 89	20	6	10	25	3
1	064 90	25	6	10	25	3
1	064 91	32	6	10	25	3
1	064 92	40	6	10	25	3
1	064 93	50	6	10	25	3
1	064 94	63	6	10	25	3


Verp.	Ref.	Tweepolig 400 V~				
		Nominale stroomst. (A)	Onderbrekingsvermogen NBN C 61-898 400 V	Onderbrekingsvermogen IEC 60947-2 (kA) 400 V	Onderbrekingsvermogen IEC 60947-2 (kA) 230 V	Aantal modules van 17,5 mm
1	064 60	1	6	10	25	2
1	064 61	2	6	10	25	2
1	064 62	3	6	10	25	2
1	064 63	4	6	10	25	2
5	064 64	6	6	10	25	2
5	064 66	10	6	10	25	2
5	064 68	16	6	10	25	2
5	064 69	20	6	10	25	2
1	064 70	25	6	10	25	2
1	064 71	32	6	10	25	2
1	064 72	40	6	10	25	2
1	064 73	50	6	10	25	2
1	064 74	63	6	10	25	2

Verp.	Ref.	Vierpolig 400 V~				
		Nominale stroomst. (A)	Onderbrekingsvermogen NBN C 61-898 400 V	Onderbrekingsvermogen IEC 60947-2 (kA) 400 V	Onderbrekingsvermogen IEC 60947-2 (kA) 230 V	Aantal modules van 17,5 mm
1	065 55	1	6	10	25	4
1	065 56	2	6	10	25	4
1	065 57	3	6	10	25	4
1	065 58	4	6	10	25	4
1	065 59	6	6	10	25	4
1	065 61	10	6	10	25	4
1	065 63	16	6	10	25	4
1	065 64	20	6	10	25	4
1	065 65	25	6	10	25	4
1	065 66	32	6	10	25	4
1	065 67	40	6	10	25	4
1	065 68	50	6	10	25	4
1	065 69	63	6	10	25	4

Hulpstukken en toebehoren (blz. 47)

Verdeling (blz. 110)

Automaten 80 tot 125 A (blz. 43)



**Aanpasbare
differentieelblokken**

www.ecatalog.be
Zie blz. 46