

BS122N

Sealed Lead-Acid Battery, 12 V, 2.2 Ah

Product overview

Sealed lead acid battery 12 V, 2.2 Ah with Fast-on 4.8 mm terminal type.



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS122N

Sealed Lead-Acid Battery, 12 V, 2.2 Ah

Technische specificaties

Algemeen

Type product	Verzegelde loodzuurbatterij
--------------	-----------------------------

Elektrische eigenschappen

Nominale spanning	12 V
Nominale capaciteit	2.2 Ah
Inwendige weerstand (circa)	42 mOhm

Opladen / ontladen

Max. laadspanning	13.8 VDC at +20°C
Max. Laadstroom	0.69 A
Max. Ontlaadstroom	11.5 A

Temperatuur

Temperatuur bij opladen	0 to +40°C
Temperatuur bij ontladen	-15 to +50°C

Fysiek

Fysieke afmetingen	178 x 34 x 60 mm
Netto gewicht	1.061 kg
Materiaal	ABS
Type aansluiting	Fast-on 4.8 mm

Omgeving

Brandvertragend	Nee
Bedrijfstemperatuur	0 to +40°C
Opslagtemperatuur	-15 to +50°C

Regelgeving

Conformiteit	CE, RoHS 2, WEEE
Certificering	VdS