



Pressverbinder

- DIN 46267, Teil 1, für zugentlastete Verbindungen
- Werkstoff: E-Cu Rohr
- Oberfläche: galvanisch verzinkt, wahlweise blank
- Reduzierhülsen zur Verbindung ungleicher Querschnitte:
Katalog Seite 2.12



Nenn- Querschnitt mm ²	Art.-Nr.*	Kenn- ziffer	Abmessung mm			Gewicht/ 100 St. ~ kg	VE/St.
			d1	d4	l		
6	121R	5	3,8	5,5	30	0,31	100
10	122R	6	4,5	6,0	30	0,34	100
16	123R	8	5,5	8,5	50	1,45	100
25	124R	10	7,0	10,0	50	1,77	50
35	125R	12	8,2	12,5	50	2,89	50
50	126R	14	10,0	14,5	56	4,26	50
70	127R	16	11,5	16,5	56	5,41	50
95	128R	18	13,5	19,0	70	8,62	25
120	129R	20	15,5	21,0	70	9,66	25
150	130R	22	17,0	23,5	80	14,50	10
185	131R	25	19,0	25,5	85	17,00	10
240	132R	28	21,5	29,0	90	23,41	10
300	133R	32	24,5	32,0	100	29,23	5
400	134R	38	27,5	38,5	150	74,32	5
500	135R	42	31,0	42,0	160	89,09	1
625	136R	44	34,5	44,0	160	79,10	1
800	137R	52	40,0	52,0	200	151,00	1
1000	138R	58	44,0	58,0	200	198,00	1

*Artikel-Nr. für Ausführung blank mit Zusatz "bk"

>> Werkzeug: siehe Tabelle Seite 2.15