

CHK-KNOPENKETING, 30 M, 400 N BELASTING

CATALOG NUMBER

CHK22K



CERTIFICATIONS



FEATURES

Veelzijdige niet-gelaste ketting met dubbele lus (knopen ketting)

Conforms to DIN 5686

PRODUCT ATTRIBUTES

Article Number: 385860

Material: Staal

Finish: Elektrolytisch gegalvaniseerd

Length: 30 m


A: 28 mm

B: 9 mm

D: 2 mm

Static Load: 400 N

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER