



BE GY16 C LIYCY 3G0,75 R1

Preflex 16mm+LIYCY-JZ Cca 323 3G0.75 C100


Properties of the article

◦ Articulenumber	1234001355
◦ Barcode	5420056255318
◦ Category	Control
◦ Gross weight (kg)	11.0
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	LIYCY JZ 3G0.75
◦ Color	
◦ Insulation	PVC
◦ CPR Class	cca s3 d2 a3

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	HD 60 364 ; EN 50575 Cca s3d2a3 ; EN 60811-501 ; EN 60811-401 ; EN 60811-404 (OLIE-HUILE) ; EN 60811-504 (KOUDE-FROID -40°C) ; EN 50290-2-22 TM54 ; EN 50290-2-21 TI52 ; EN 60216

Certificates

