


Reductie, metrische schroefdraad



M

Reductie (deel H) conform DIN 46320, met metrische schroefdraad conform DIN EN 60423 resp. ISO 68.

* Prijzen volgens DEL-notering.

Type	Schroefdraad buiten	Schroefdraad binnen	Afm. D mm	Schroefdraad- lengte mm	Afm.L2 mm	Verp. Stuk	Gewicht kg/100 st.	Bestelnr.
167 R MS M16-12	M16	M12	20	6	8,5	50	0,880	2089505
167 R MS M20-12	M20	M12	24	6,5	9	50	1,340	2089513
167 R MS M20-16	M20	M16	24	6,5	9	50	1,480	2089521
167 R MS M25-16	M25	M16	30	7	10	50	3,220	2089548
167 R MS M25-20	M25	M20	30	7	10	50	2,700	2089556
167 R MS M32-20	M32	M20	39	8	11,5	50	6,120	2089564
167 R MS M32-25	M32	M25	39	8	11,5	50	4,500	2089572
167 R MS M40-25	M40	M25	50	6	12,5	25	9,960	2089580
167 R MS M40-32	M40	M32	50	9	12,5	25	6,840	2089599
167 R MS M50-32	M50	M32	57	10	14	25	16,300	2089602
167 R MS M50-40	M50	M40	57	10	14	25	10,250	2089610
167 R MS M63-40	M63	M40	64	10	14	10	30,080	2089629
167 R MS M63-50	M63	M50	64	10	14	10	10,090	2089637

CuZn messing

N vernikkeld

Afmetingen

