

### Product type designation

Product description

### PROFIBUS bus connector RS 485

Bus connector with axial cable outlet (180°)

PROFIBUS bus connector with axial cable outlet for Industry PC, SIMATIC OP, OLM; Transmission rate 12 Mbit/s; terminating resistor with isolating function, Metal enclosure



Suitability for use	For connecting PROFIBUS nodes to the PROFIBUS bus cable
<b>Transfer rate</b>	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
<b>Interfaces</b>	
Number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Terminal blocks
• for network components or terminal equipment	Sub-D connector (9-pin)
Type of electrical connection / FastConnect	No
<b>Mechanical data</b>	
Design of terminating resistor	Integrated resistor combination that can be selected with slide switch. Disconnect function: When the resistor is connected, the outgoing bus is isolated.
Material / of the enclosure	metal
Locking mechanism design	Screw

## Design, dimensions and weight

Type of cable outlet	180° cable outlet
Width	15 mm
Height	57 mm
Depth	39 mm
Net weight	100 g

## Ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-25 ... +80 °C
• during transport	-25 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	75 %
Protection class IP	IP20

## Product features, product functions, product components / general

Product feature	
• silicon-free	Yes
Product component	
• PG connection socket	No
• strain relief	Yes

## Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• UL approval	No
• cULus approval	No
• Railway application in accordance with EN 50155	No

## Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx Download Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	12/14/2019