



## BE GY20 C XVB 5G2,5 R1

Preflex 20mm+XVB Cca (a3d2s3) 5G2.5 C100

### Properties of the article

◦ Articulenumber	1234000449
◦ Barcode	5420056256193
◦ Category	Energy & Light
◦ Gross weight (kg)	27.1
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

### Properties of the Preflex<sup>®</sup> tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	XVB 5G2.5
	
◦ Color	
◦ Insulation	PVC
◦ CPR Class	cca s3 d2 a3

### Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575

### Certificates

