

fuser_200_a_1_caf



NFC en DIN - Rechtstreekse bediening 160 tot 400 A

Kaliber(A) / Zekering / Grootte van de behuizing	Aantal polen	Naakt toestel	Rechtstreekse handgreep	Hulpcontact	Klemafdekking	Hulpcontact doorsmelten zekering				
160 A / 0 / 4	2 P	3615 2016	Zwart 3629 7901 ⁽⁵⁾⁽²⁾	Type A 1 contact OG 3999 0021 ⁽³⁾ Type A 2 contacten OG 3999 0022 ⁽³⁾	2 P 3998 2016 ⁽⁴⁾	3994 0216				
	3 P	3615 3016			3 P 3998 3016 ⁽⁴⁾	3994 0316				
	4 P	3615 6016			4 P 3998 4016 ⁽⁴⁾	3994 0416				
250 A / 1 / 5	2 P	3615 2024			Zwart 3629 7901 ⁽⁵⁾⁽²⁾	Type A 1 contact OG 3999 0021 ⁽³⁾ Type A 2 contacten OG 3999 0022 ⁽³⁾	2 P 3998 2025 ⁽⁴⁾	1 ^o contact OG 2 P		
	3 P	3615 3024					3 P 3998 3025 ⁽⁴⁾	3994 0225 1 ^o contact OG		
	4 P	3615 6024					4 P 3998 4025 ⁽⁴⁾	3 P 3994 0325 1 ^o contact OG		
400 A / 2 / 6	2 P	3615 2039					Zwart 3629 7901 ⁽⁵⁾⁽²⁾	Type A 1 contact OG 3999 0021 ⁽³⁾ Type A 2 contacten OG 3999 0022 ⁽³⁾	4 P 3998 4025 ⁽⁴⁾	4 P 3994 0425
	3 P	3615 3039								
	4 P	3615 6039								

- (1) Rechtstreekse frontale bediening.
 (2) Standaard.
 (3) Maximaal 2 contacten.
 (4) Opwaarts of afwaarts.
 (5) Rechtstreekse laterale rechtse bediening.
 (6) Maximaal 8 contacten.

fuser_416_a_1_caf



NFC en DIN - Rechtstreekse bediening 630 tot 1250 A

Kaliber(A) / Zekering / Grootte van de behuizing	Aantal polen	Naakt toestel	Rechtstreekse handgreep	Hulpcontact	Klemafdekking	Hulpcontact doorsmelten zekering						
630 A / 3 / 17	2 P	3811 2063	Zwart 3899 6011 ⁽¹⁾⁽²⁾	Type U 1 contact G 3999 0701 ⁽³⁾ Type U 1 contact O 3999 0702 ⁽³⁾		3894 1206						
	3 P	3811 3063			2 P 3898 2080 ⁽⁴⁾	3894 1306						
	4 P	3811 6063			3 P 3898 3080 ⁽⁴⁾	3894 1406						
800 A / 3 / 17	2 P	3811 2080			Zwart 3899 6011 ⁽¹⁾⁽²⁾	Type U 1 contact G 3999 0701 ⁽³⁾ Type U 1 contact O 3999 0702 ⁽³⁾	4 P 3898 4080 ⁽⁴⁾					
	3 P	3811 3080										
	4 P	3811 6080										
800 A / 4 / 18	2 P	3811 2081					Zwart 3899 7011 ⁽¹⁾⁽²⁾	Type U 1 contact G 3999 0701 ⁽³⁾ Type U 1 contact O 3999 0702 ⁽³⁾		1 ^o contact OG 2 P		
	3 P	3811 3081							2 P 3898 2120 ⁽⁴⁾	3894 1212 1 ^o contact OG		
	4 P	3811 6081							3 P 3898 3120 ⁽⁴⁾	3 P 3894 1312		
1250 A / 4 / 18	2 P	3811 2120							Zwart 3899 7011 ⁽¹⁾⁽²⁾	Type U 1 contact G 3999 0701 ⁽³⁾ Type U 1 contact O 3999 0702 ⁽³⁾	4 P 3898 4120 ⁽⁴⁾	1 ^o contact OG 4 P
	3 P	3811 3120										3894 1412
	4 P	3811 6120										

- (1) Standaard.
 (2) Rechtstreekse frontale bediening.
 (3) Maximaal 8 contacten.
 (4) Opwaarts of afwaarts.