



## BE BL16 E UTP6 H3

Preflex 16mm+U/UTP Eca CAT6 D300

### Properties of the article

◦ Articulenumber	1234001257
◦ Barcode	5420056261869
◦ Category	Data
◦ Gross weight (kg)	25.5
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Reel Ø 60 cm
◦ Length	300

### Properties of the Preflex<sup>®</sup> tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Blue
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	U/UTP CAT6
◦ Color	
◦ Insulation	
◦ CPR Class	eca

### Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575

### Certificates

