



## BE BL20 E 2xUTP5E R1

Preflex 20mm+2xU/UTP Eca CAT5E C100

### Properties of the article

◦ Articlenumber	1234001270
◦ Barcode	5420056263948
◦ Category	Data
◦ Gross weight (kg)	13.6
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Roll
◦ Length	100

### Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Blue
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	U/UTP CAT5E	U/UTP CAT5E
◦ Color		
◦ Insulation		
◦ CPR Class	eca	

### Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575

### Certificates

