

PRODUCT-DETAILS

## 6583-500

# 6583-500 Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI)



### Algemene informatie

Type	6583-500
Artikelnummer	2CKA006590A0178
EAN	4011395066928
Omschrijving	6583-500 Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI)
Omschrijving	<p>Universal Central Dimmer modular. For switching and dimming of incandescent lamps, 230 V halogen incandescent lamps and low-voltage halogen lamps with conventional or electronic transformers. With light-level memory, adjustable minimum brightness and with intelligence for universal operation. Capacity expansion via output-side parallel-connected load line (with RJ 12 plug) with a power module 6584 (max. 6 pcs = 3000 W/VA total wattage). Compatible with control module 6597 and ABB Powernet KNX in combination with control module 6997/60. Operation using a plug-in push switch/rotary and timer control cover 6543/10, ..11, --12 and/or a conventional push switch (2020 US or 2021/6 UK or Rotary Dimmer insert for combination with flush-mounted inserts 6592 U. Low-noise, short-circuit-proof, overload-protected.</p>

### Technical

Geschikt voor	2CKA006590A0179 2CKA006590A0155 2CKA006590A0181 2CKA006590A0183 2CKA006590A0185 2CKA006198A0102 2CKA006900A1659 2CKA001413A0475 2CKA001413A0897
Toegekende spanning (U <sub>r</sub> )	230 V

Nominaal stuurvoltage (U <sub>s</sub> )	220...240 V
Hulpspanning AC/DC	230 V AC/DC
Frequentie (f)	50...60 Hz
Toegekende frequentie (f)	50...60 Hz
Lampvermogen	60...500 V·A
Productreeks	Busch-Dimmer®
Aansluitwijze	Screw Clamp
Belastingwijze	Universal
Montagetype	Mounted Din Rail Component
Soort bevestiging	Mounting with Claw
Uitvoering oppervlakte	Surface protection: Untreated Surface finishing: Matt
Materiaal	Material quality: Thermoplastic (3) Material: Plastic (3)
RAL-nummer	RAL 7035 - Lichtgrijs
Battery Weight	0 g
Aantal batterijen	0

## Environmental

Omgevingsluchttemperatuur	Operation 0 ... +45 °C
RoHS-status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Dimensions

Breedte in module-eenheden	2
Product netto gewicht	0.123 kg

## Container Information

Pakketniveau 1 Units	1 stuk
Pakketniveau 1 Breedte	92 mm
Pakketniveau 1 Hoogte	58 mm
Pakketniveau 1 Lengte	78 mm
Pakketniveau 1 Brutogewicht	0.188 kg
Pakketniveau 1 EAN	4011395066928
Pakketniveau 2 Units	10 stuk
Pakketniveau 2 Breedte	168 mm
Pakketniveau 2 Hoogte	112 mm
Pakketniveau 2 Lengte	298 mm
Pakketniveau 2 Brutogewicht	2.005 kg

## Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85365080
E-Number (Sweden)	1360020
Vervangen product-ID (NIEUW)	2CKA006590A0193
Land van herkomst	Germany (DE)

### Certificates and Declarations (Document Number)

Conformiteitsverklaring - CE	2CKA100000E1696
Instructies en handleidingen	DEBJE-6583-6584_ABB_OA_2012-12-17_DE_R01
REACH Declaration	2CKA309999E9999
RoHS-informatie	9AKK104295D8727

### Popular Downloads

Instructies en handleidingen	DEBJE-6583-6584_ABB_OA_2012-12-17_DE_R01
------------------------------	--

### Classifications

ETIM 7	EC000025 - Dimmer
ETIM 8	EC000025 - Dimmer
EPLAN-catalogus boom	Electrical engineering / Sensor, switch, and pushbutton / Switch , pushbutton
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144014

### Categorieën

Laagspanningsproducten en -systemen → Switch Assortments → Light / LoadControl → Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI) → Rotary Dimmer - DIN Rail

