

PRODUCT-DETAILS

BE/S8.20.2.1

BE/S8.20.2.1 Binary Input, 8-fold, Contact Scanning, MDRC



Algemene informatie

Type	BE/S8.20.2.1
Artikelnummer	2CDG110092R0011
EAN	4016779710763
Omschrijving	BE/S8.20.2.1 Binary Input, 8-fold, Contact Scanning, MDRC
Omschrijving	The device interrogates 8 floating contacts using an internally generated scanning voltage. State inputs via 8 LEDs. Max. 8 signals are detectable. Each channel one push button for manual operation. Supplied by ABB i-bus®.

Ordering

EAN	4016779710763
Numer douanetarief	85371091
Minimale bestelhoeveelheid	1 stuk
E-Number (Switzerland)	405608305
E-Number (Finland)	2815306
E-Number (Sweden)	1750246

Dimensions

Product netto diepte	64.5 mm
Product netto hoogte	90 mm
Product netto breedte	72 mm
Product netto gewicht	0.2 kg

Container Information

Pakketniveau 1 Units	box 1 stuk
Pakketniveau 1 EAN	4016779710763
Pakketniveau 1 Lengte	77 mm
Pakketniveau 1 Hoogte	65 mm
Pakketniveau 1 Breedte	92 mm
Pakketniveau 1 Brutogewicht	0.23 kg

Technical

Compatibele bussystemen	KNX (TP)
Beschermingsgraad	IP20
Montagetype	DIN-Rail
Breedte in module- eenheden	4

Certificates and Declarations (Document Number)

CB-certificaat	9AKK107991A3185
Gegevensblad, technische informatie	2CDC504041D0202 2CDC504078D0202
Conformiteitsverklaring - CE	2CDK504020D2701
Instructies en handleidingen	2CDG941070P0005
RoHS-informatie	2CDK504020D2701

Environmental

RoHS-status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Classifications

ETIM 7	EC000688 - Binary input for bus system
ETIM 8	EC000688 - Binary input for bus system
eClass	V11.0 : 27143121
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)

Categorieën

Laagspanningsproducten en -systemen → Gebouwautomatisering → KNX → Standaardingen → Binaire ingangen
contactscannen

