

PRODUCT-DETAILS

BE/S4.20.2.1

BE/S4.20.2.1 Binary Input, 4-fold, Contact Scanning, MDRC



Algemene informatie

Type	BE/S4.20.2.1
Artikelnummer	2CDG110090R0011
EAN	4016779710787
Omschrijving	BE/S4.20.2.1 Binary Input, 4-fold, Contact Scanning, MDRC
Omschrijving	The device interrogates 4 floating contacts using an internally generated scanning voltage. State inputs via 4 LEDs. Max. 4 signals (in 2 groups) are detectable. Each channel one push button for manual operation. Supplied by ABB i-bus®.

Ordering

EAN	4016779710787
Numer douanetarief	85389091
Minimale bestelhoeveelheid	1 stuk
E-Number (Switzerland)	405607305
E-Number (Finland)	2815304
E-Number (Sweden)	1750242

Dimensions

Product netto diepte	64.5 mm
Product netto hoogte	90 mm
Product netto breedte	36 mm
Product netto gewicht	0.1 kg

Container Information

Pakketniveau 1 Units	box 1 stuk
Pakketniveau 1 EAN	4016779710787
Pakketniveau 1 Lengte	41 mm
Pakketniveau 1 Hoogte	65 mm
Pakketniveau 1 Breedte	92 mm
Pakketniveau 1 Brutogewicht	0.12 kg

Technical

Compatibele bussystemen	KNX (TP)
Beschermingsgraad	IP20
Montagetype	DIN-Rail
Breedte in module- eenheden	2

Certificates and Declarations (Document Number)

CB-certificaat	9AKK107991A3185
Gegevensblad, technische informatie	2CDC504041D0202 2CDC504076D0202
Conformiteitsverklaring - CE	2CDK504018D2701
Instructies en handleidingen	2CDG941070P0005
RoHS-informatie	2CDK504018D2701

Environmental

RoHS-status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Classifications

ETIM 7	EC000688 - Binary input for bus system
ETIM 8	EC000688 - Binary input for bus system
eClass	V11.0 : 27143121
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)

Categorieën

Laagspanningsproducten en -systemen → Gebouwautomatisering → KNX → Standaardingen → Binaire ingangen
contactscannen

