PRODUCT-DETAILS

JRA/S 4.24.5.1

JRA/S4.24.5.1 Blind/Roller Shutter Act, Travel Det, 4-f, 24 V DC, Man Op, MDRC

Algemene informatie

Type	JRA/S 4.24.5.1
Artikelnummer	2CDG110128R0011
EAN	4016779698474
Omschrijving	JRA/S4.24.5.1 Blind/Roller Shutter Act, Travel Det, 4-f, 24 V DC, Man Op, MDRC
Omschrijving	For the control of up to 4 independent 24 V DC drives via ABB i-bus® KNX. The device is designed for positioning blinds, roller shutters, awnings and other shading products as well as for controlling doors, windows and ventilation flaps. Additional auxiliary voltage is not needed. The travel times of the drive are detected automatically via current detection. Push buttons are located at the front of the device to control the outputs e.g. during commissioning. The current status of the output is displayed via LEDs.

Ordering

EAN	4016779698474
Nummer douanetarief	85371091
Minimale bestelhoeveelheid	1 stuk
E-Number (Switzerland)	405430445
E-Number (Finland)	2815402
E-Number (Sweden)	1751252

Dimensions

Product netto diepte	64.5 mm

Product netto hoogte	90 mm
Product netto breedte	72 mm
Product netto gewicht	0.22 kg

Container Information

Pakketniveau 1 Units	box 1 stuk
Pakketniveau 1 EAN	4016779698474
Pakketniveau 1 Lengte	77 mm
Pakketniveau 1 Hoogte	65 mm
Pakketniveau 1 Breedte	92 mm
Pakketniveau 1 Brutogewicht	0.252 kg

Technical

Compatibele bussystemen	KNX (TP)
Beschermingsgraad	IP20
Montagetype	DIN-Rail
Breedte in module-eenheden	4

Certificates and Declarations (Document Number)

CB-certificaat	9AKK107991A3191
Gegevensblad, technische informatie	2CDC506040D0201 2CDC506064D0202
Conformiteitsverklaring - CE	2CDK506043D2701
Instructies en handleidingen	2CDG941079P0005
RoHS-informatie	2CDG510125-0100

Environmental

RoHS-status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Classifications

ETIM 7	EC001330 - Shutting actuator for bus system
ETIM 8	EC001330 - Shutting actuator for bus system
eClass	V11.0 : 27143128
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)

Categorieën

Laagspanningsproducten en -systemen → Gebouwautomatisering → KNX → Bediening van zonweringen → Jaloezieaandrijvingen 24 V DC