



WEVER & DUCRÉ
LIGHTING

TUBE WALL 2.0 PAR16

711220B0

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Surface
Jet Black
IP65
Exterior
Indirect 355^a to 360^b lm
Direct 355^a to 360^b lm
Total 710^a to 720^b lm
RAL 9005^c

LED

Lamp 2 x PAR16
PAR16
Socket GU10
max. 5 W
CRI 80

PHYSICAL

Diameter 80 mm
Height 152 mm
0.67 kg

ELECTRICAL

100 - 240 V
Total connected power 8.2^b to 9.7^a W
Class 1
Safety distance 0.3 m


^a PAR16 LED 2700K CRI 80 silver

^b LED 3000K CRI 80 silver


^c Color may deviate slightly due to production conditions.



IP65 <math>\pm 0,3>



LIGHT DISTRIBUTION



[711220B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

TUBE WALL 2.0 PAR16

711220B0

LAMPS

PAR16 LED Lamp

TYPE	Ø · H (MM)	ORDERCODE
2700K >80 CRI GU10	∅50 · 52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	∅50 · 52	9 0 5 2 2 7 S 4