







# BOX

## OUTDOOR WALL SURFACE



### 1.0

LED 6W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
incl. flaps for adjustable beam angle

0.60kg IP65

CODE
740168W
740168Q
740168D
740168B

#### Light Colour Selection

LUMEN	CRI	CODE
2700K	400	>80 2
3000K	440	>80 4

### 2.0

2xLED 3W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
incl. flaps for adjustable beam angle

0.66kg IP65

CODE
740148W
740148Q
740148D
740148B

#### Light Colour Selection

LUMEN	CRI	CODE
2700K	2x200	>80 2
3000K	2x220	>80 4

### 3.0

LED 6W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
incl. flaps for adjustable beam angle

0.67kg IP65

CODE
740268W
740268Q
740268D
740268B

#### Light Colour Selection

LUMEN	CRI	CODE
2700K	400	>80 2
3000K	440	>80 4

### 4.0

2xLED 3W | 220-240VAC | 50-60Hz  
PCB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
incl. flaps for adjustable beam angle

0.86kg IP65

CODE
740248W
740248Q
740248D
740248B

#### Light Colour Selection

LUMEN	CRI	CODE
2700K	2x200	>80 2
3000K	2x220	>80 4