


TIM

Draadstang (DIN 975) / Tige filetée (DIN 975)



Stand. Uitv./Exec. Std.

Elektrolytisch verzinkt/Electro Zingué

Artikel Référence	Max. Belasting (in daN) Charge max. (en daN)
TIM6	300
TIM8	550
TIM10	900
TIM12	1300

HD	Artikel Référence	↕ mm	↔ mm	↔ mm	↔ mm	kg/m	⊞	Stock Magasin	Eenheid Unité
-	TIM6	-	-	M6	2000	0,170	50	✓	m
-	TIM8	-	-	M8	2000	0,310	20	✓	m
-	TIM10	-	-	M10	2000	0,460	20	✓	m
-	TIM12	-	-	M12	2000	0,700	10	✓	m


Te bevestigen met:
A fixer avec:

HD	M8	-	-	M8	-	0,010	250	✓	st/pc
HD	M10	-	-	M10	-	0,010	250	✓	st/pc
HD	M12	-	-	M12	-	0,020	250	✓	st/pc
HD	RO8	-	-	M8	-	0,010	250	✓	st/pc
HD	RO10	-	-	M10	-	0,010	250	✓	st/pc
HD	RO12	-	-	M12	-	0,010	250	✓	st/pc

5

VM6334

Verbindingsmof (DIN 6334) / Manchon de jonction tige fil. (DIN 6334)



Stand. Uitv./Exec. Std.

Elektrolytisch verzinkt/Electro Zingué

HD	Artikel Référence	↕ mm	↔ mm	↔ mm	↔ mm	kg/st kg/pc	⊞	Stock Magasin	Eenheid Unité
-	VM6	18	-	M6	-	0,010	48	✓	st/pc
-	VM8	24	-	M8	-	0,020	48	✓	st/pc
-	VM10	30	-	M10	-	0,040	48	✓	st/pc
-	VM12	36	-	M12	-	0,060	48	✓	st/pc