

# Product data sheet

DEECOS S MINI


741934.003.1

RZB



Series: Deecos Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Gehäuse Aluminium-Druckguss pulverbeschichtet. 356° horizontal dreh- und 90° vertikal schwenkbar. Thermobeständiger Kunststoffring schwarz. Mit Optikbaugruppe Reflektor aus MIRO-SILVER mit 98% Lichtgesamtreflexion. Passive Kühlung. Mit Multi-Adapter für 3-Phasen-Stromschienen 230 V. Leuchtmittel (LED) im Lieferumfang enthalten. Available Colours: deep black, matt (RAL 9005) Type of Installation: Track on ceiling Dimensions: L 97, B 87, H 214 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 2900lm System power: 34W Beam Angle: 18° Number of fittings B10A: 15 Number of fittings B16A: 24 Number of fittings C10A: 24 Number of fittings C16A: 40 Inrush current: 22A Unified Glare Ratio: 16,3 EEC: A+

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 34 W    | CRI         | 90     |
| Total flux         | 2900 lm | LOR         | 100%   |
| Luminous efficacy  | 85 lm/W | Total power | 34 W   |

## Mounting mode

Ceiling mounted

## Electric

System power: 34 W

## Shape and measurements

Length: 87 mm

Width: 97 mm

Height: 214 mm

## Protection

IP: 20

IK: 06

## Adjustability

Rotatable, Tilttable

## Design

Colour of housing: Black