



Residual current circuit breaker (RCCB), 40A, 2pole, 300mA, type A

Type PFIM-40/2/03-A-MB
Artikel nr. 274042
Catalog No.

Technische gegevens ETIM 5.0

Veiligheidsschakelaars en zekeringen (EG000020) / Aardlekschakelaar (EC000003)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB) (ec ss8-27-14-22-01 [AAB906010])			
Aantal polen			2
Nom. (meet)spanning	V		230
Nom. (meet)stroom	A		40
Nom. foutstroom	A		0.3
Montagewijze			DIN-rail (DRA)
Type lekstroom			A
Selectieve bescherming			Nee
Kortsluitvastheid (Icw)	kA		10
Nom. afschakelvermogen EN 60898	kA		0.5
Nom. afschakelvermogen IEC 60947-2	kA		0
Stootspanningsvastheid	kA		0.25
Frequentie			50 Hz
Nevenapparaat mogelijk			Ja
Beschermingsgraad (IP)			IP20
Maat (conform DIN 43880)			1
Breedte in module-eenheden			2
Inbouwdiepte	mm		70.5
Kortstondigvertraagd type			Nee