



Residual current circuit breaker (RCCB), 63A, 4pole, 300mA, type A

Type PFIM-63/4/03-A-MB
Artikel nr. 274054
Catalog No.

Technische gegevens ETIM 5.0

Veiligheidsschakelaars en zekeringen (EG000020) / Aardlekschakelaar (EC000003)

Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB)
(ecl@ss8-27-14-22-01 [AAB906010])

Aantal polen			4
Nom. (meet)spanning		V	400
Nom. (meet)stroom		A	63
Nom. foutstroom		A	0.3
Montagewijze			DIN-rail (DRA)
Type lekstroom			A
Selectieve bescherming			Nee
Kortsluitvastheid (Icw)		kA	10
Nom. afschakelvermogen EN 60898		kA	0.6
Nom. afschakelvermogen IEC 60947-2		kA	0
Stootspanningsvastheid		kA	0.25
Frequentie			50 Hz
Nevenapparaat mogelijk			Ja
Beschermingsgraad (IP)			IP20
Maat (conform DIN 43880)			1
Breedte in module-eenheden			4
Inbouwdiepte		mm	70.5
Kortstondigvertraagd type			Nee