BE LGN16 LS C Z1U 5G1,5 Std R1

Prf SAFE 16mm+HO7Z1-U Cca(a1d1s1)5G1.5 G/Y BL BR BLA GR C100

Properties of the article

Articlenumber	1234000586
Barcode	5420056254090
Category	Energy & Light
Gross weight (kg)	14.8
Dimensions (WxLxH)	500 x 500 x 200 MM
Packaging	Roll
Length	100

Properties of the Preflex® tube

Material of tube	Halogen-free Polypropylene
Color	Light Green
Outer diameter (mm)	16
Inner diameter (mm)	10.6
Classification	ICTA 3422
Pressure resistance	750N / 23°C
Impact resistance	6J / -5°C
Breakthrough test	2000V / 50-60 Hz 15min.
Insulation resistance	min. 100 Mohm/80cm
Test temperature	-5°C tot +90°C
Min. installation temperature	-5°C

Characteristics of the cable or cable combination

Cable type	H07Z1-U 5G1.5
Color	
Insulation	LS0H
CPR Class	cca s1 d1 a1

Certificates

Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
Norm van de kabel	EN 50565-1 ; EN 50565-2

Certificates